



PocketPOS™ P200 technical specifications

Available in "3G", "GPRS" and "Wifi" versions

| | |
|---------------------------------------|--|
| Processor | 32 bit Highly Secure CPU |
| Memory | 16MB SDRAM, 16MB Nor-Flash |
| Display | 128x64, Built-in Icons, Backlight |
| Sound | Multi-tone Beeper |
| Keypad | 18 Keys, Clear Plastic |
| LED's | Four LED's (Green, Yellow, Blue and Red) |
| Communication Ports | USB (USB 2.0, Slave, Mini-USB B) Serial (RS232) Bluetooth (Class 2 - 10 meter, V2.1+EDR) |
| Available Communication Module | 850/900/1800/1900 GPRS Module |
| Battery/Power | 1800mAh, 7.4V, Lithium-Polymer battery 1000mAh, 7.4V, Lithium-Polymer battery (available in Printerless Version) AC charging adapter 100-240VAC, 50/60 Hz |
| Printer | 48mm, 203dpi, thermal printer (optional) |
| Paper Size | 58mm / 2.3 in (width), 30mm / 1.2 in (roll diameter) |
| Card Reader | MSR (ISO-7811, 1/2/3 track, Bi-directional) IC card Reader (ISO-7816, EMV/T=0 & T=1) SAM Module (ISO-7816, 5V) |
| Certifications | EMV Level1 Level2 PCI PTS 3.0 FCC、CE |
| RTC | Built-in |
| Key Management | DUKPT |
| Apple MFi support | iPad, iPhone, iPod Touch (iOS 4.0 or higher) |
| Dimensions(W x D x H) | 79×146×37mm / 3.1×5.7×1.5" 79×146×42mm / 3.1×5.7×1.7" (3G/GPRS/Wifi) |
| Weight | 400g / 14.1oz / 0.88 lbs (paper and battery included) (Bluetooth) 408g / 14.4oz / 0.90 lbs (paper and battery included) (3G/GPRS/Wifi) |
| Environment | Operating temperature: 0 ~ 40°C (+32 ~ 104°F) Operating humidity: 20 ~ 85% RH Storage temperature: -20 ~ 60°C (-4 ~ 140°F) Storage humidity: 10~ 90% RH |

All features and specifications are subject to change without notice. All trademarks mentioned are registered by their respective owners. Contact Blue Bamboo sales for more details.

Blue Bamboo Corporate Offices
5 Floor, Huishan Technology Park,
3333 Changning Road, Shanghai China 200336
Tel: +86 21 5219 0333 Fax: +86 21 5219 0603
USA Office Tel: 1-888-372-9266

